

DIGITAL TV APPLICATIONS



3A2NCQ: COAXIAL CIRCULATOR 470 TO 600 MHZ

FREQUENCY GHz	ISOLATION dB, MIN	INSERTION LOSS dB, MAX	VSWR MAX	POWER, WATTS CW	TEMPERATURE RANGE
470-600	20	0.400	1.250:1	300	0° TO +50°C
SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.					

3A2NCG: COAXIAL CIRCULATOR 600 TO 800 MHZ

FREQUENCY GHz	ISOLATION dB, MIN	INSERTION LOSS dB, MAX	VSWR MAX	POWER, WATTS CW PK	TEMPERATURE RANGE
600-800	20	0.350	1.250:1	300 500	0°C TO +85°C
SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.					

TYPICAL PACKAGE DIMENSIONS



PCS & CELLULAR APPLICATIONS

2A2NBG: COAXIAL ISOLATOR 869 TO 894 MHZ

FREQUENCY (MHz)	ISOLATION (dB) MIN	INSERTION LOSS (dB) MAX	VSWR MAX	POWER (WATTS) PK AVE	TERMINATION (WATTS)	POWER MONITOR	TEMPERATURE RANGE
869-894	23	0.200	1.150:1	300 150	30	1+/- .5VDC @30 WATTS	-30°C TO +80°C
SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.							

2A4NDC: COAXIAL ISOLATOR 1.840 TO 1.870 MHZ

FREQUENCY (MHz)	ISOLATION (dB) MIN	INSERTION LOSS (dB) MAX	VSWR MAX	POWER (WATTS) PK AVE	TERMINATION (WATTS)	POWER MONITOR	TEMPERATURE RANGE
1.840-1.870	23	0.200	1.150:1	300 60	30	1+/- .5VDC @30 WATTS	-30°C TO +70°C
SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.							

