

Communications & Power Industries Power Supplies

CPI Beverly Microwave Division manufactures CW, TWT power supplies for use in Electronic Warfare electronic counter measures and radar applications.

FEATURES:

- High altitude compliant
- Small, condensed supplies
- Airborne qualified
- Pod mounted capability

BENEFITS:

- High reliability
- Rugged for airborne military environment

APPLICATIONS:

- Airborne radars
- EW applications
- Radars



Typical Operating Parameters

Frequency (GHz)	Peak Power	Operating Voltage	Operating Temperatures	Altitude	VED Type
X-Band	800 Watts	2750V	-45 to +88 degrees C	70,000 ft	Magnetron
I/J-Band	50-100 Watts	4400V (cathode)	-30 to +60 degrees C	10,000 ft	Helix TWT
Ku-Band	400 Watts (pulsed)	28VDC	-40 to +_70 degrees C	36,000 ft	Booster Helix TWT
Low band	400-1000 Watts	4.4 kV	-30 to +80 degrees C	50,000 ft	Helix TWT

Power levels and frequencies are dependent on the TWT selected



Beverly Microwave Division
150 Sohier Road
Beverly, Massachusetts
USA 01915

tel +1 978-922-6000
email BMDMarketing@cpii.com
fax +1 978-922-8914
web www.cpii.com

For more detailed information, please refer to the corresponding CPI technical description if one has been published, or contact CPI. Specifications may change without notice as a result of additional data or product refinement. Please contact CPI before using this information for system design.

©2020 Communications & Power Industries LLC. Company proprietary; use and reproduction is strictly prohibited without written authorization from CPI.